

14TUT | "Texas" Utility

Shown with Optional Spare Mount

GVWR: 9,890 lbs
BED LENGTHS: 14' - 24'
BED WIDTH: 82"



GATE OPTION
48" Reinforced, Spring Assisted Tractor Gate with ergonomic lift handles.


TOP RAIL CHOICES
2-3/8" PIPE with **BALLED ENDS:** Permanently sealed and ergonomic
3" x 2" x 3/16" ANGLE IRON
or 2" SQ. TUBE

FLOOR
2" Treated Lumber, installed **AFTER** painting to ensure no framing is left unfinished. Floor is secured with 5/16" screws and a bolt-on board cap.

SEALED WIRING HARNESS
with molded 7-way plug

JACK
2000 lb Capacity Top-Wind Jack with foot, Bolted-on

FENDERS
Tear Drop Fenders (added strength & durability)


DEXTER AXLE
2 - 5200 lb E-Z Lube, for quick and easy lubrication, with 1 Electric Brake

TIRES
ST225/75D15
15" x 6 Hole Wheels



COUPLER
2-15/16" - 12,500 lb Sleeve-Lock

FULL WRAP TONGUE: 5" Channel
The most vulnerable part of any trailer frame is the midsection in front of the axles. All Diamond C tandem axle trailers have a full-wrap tongue which reinforces the frame all the way to the front fender brace.

ALL RUBBER-MOUNTED LED LIGHTS

FRAME & CROSS MEMBERS
4" Channel Frame with 2" x 11 ga square tube Cross-Members (22'-24' Require 5" Channel Frame Upgrade)

STAKE POCKETS
6 Stake Pockets used as tie down points



Diamond C uses road-tested DuPont polyurethanes that provide the trailers with a long-lasting, rugged, and beautiful finish.

Specifications, standard features, options, components, and colors are subject to change without notice. Some features may be subject availability, delays, or discontinuance.

Standard Premium Dupont Paint Colors
Custom colors available upon request.

